



Promax 10000T

Powered by 21hp Vanguard engine for performance, durability and reliability. These generators feature heavy duty roll-frame that suits any worksite. The automatic voltage regulator and circuit breaker help maintain safe and steady voltage.

Features



Powered by VANGUARD™

World class durability and emissions.



Highest capacity fuel tank in category

Longest run time.



Specifications

Model Number

030509

Engine Type

Air cooling, 4 Strokes, OHV, gasoline engine

Engine Displacement (cc)

627.0

Fuel Tank Capacity

40.0

Frequency

50.0

Max Watts @50Hz (kVA)**

13.0

Amperage (A)

14.5x3

Automatic Voltage Regulation

Yes

Voltage Meter

Yes

Low Oil Sensor

Yes

Product Width (mm)

685

Weight (kg)

195

Engine Brand

Vanguard™ V-Twin

Gross Horsepower (hp)*

21.0

Starting System

Electric

Phase

3-Phase

Rated Watts @50Hz (kVA)**

12.0

Voltage (V)



380/220

Power Factor

PF0.8

Run Time Meter

Yes

Current Meter

Yes

Product Length (mm)

985

Product Height (mm)

810

Engine Series

M38

**All power levels are stated ft-lbs torque (or gross horsepower) per SAE J1940 as rated by Briggs & Stratton.*

***Generators are rated in accordance with CSA (Canadian Standards Association) standards C22.2 No. 100-04 (motors and generators). OSHA regulations may require the use of models with GFCI protected outlets on job sites.*